



## AMHMI138CX



VIDEO

### Product Description

Inspection Window Kit 13" x 8"

**Cover Type:** Lift-Off 10-Screw Clear Cover

**Catalog #:** AMHMI138CX

**Height:** 14.7 in.

**Width:** 9.7 in.

**Depth:** 0.6 in.

**Usable Depth:** 0.47 in.

**Carton Quantity:** 1

**Carton Weight:** 2 lb.

**UPC:** 085339975441

**UNSPSC:** 39121302

**Country of Origin:** United States of America

### FEATURES

Rigid clear window design with a gasket system encased in a continuous channel to provide an inspection point to see inside the enclosure, but also seal to the exterior of the enclosure and maintain it's intended rating. UL recognized component for use with NEMA 4X enclosures.

### APPLICATION

Inspection window for use on the exterior walls of NEMA Type 4X enclosures which allows the end user a viewing hole to see important equipment housed inside without having to access the enclosure.

### STANDARDS

Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. [E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 3, 3R, 4, 4X, and 12.

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



Meets Requirements: ANSI/UL50, ANSI/UL50E, and ANSI/UL508A; File No. [E487574](#)

UL® listed and recognized component for use with CSA® listed enclosure products Types 1, 2, 3, 3R, 4, 4X, 12 and 13.

Complies With:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



### COLOR

Clear Polycarbonate

### MATERIAL

Polycarbonate

### MOUNTING

10 screws

### ADDITIONAL MATERIALS

Plated carbon steel internal hardware

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system