# AMU1648NLF



# **Product Description**

Wall mount enclosure assembly

Cover Type: Nonmetal Snap Latch Hinged Solid/Opaque Cover

**Brand:** ULTRALINE® Carton Quantity: 1 Carton Weight: 11 lb. Catalog #: AMU1648NLF

Height: 16.05 in. UPC: 085339998280 Width: 14.27 in. UNSPSC: 39121324 Depth: 8 in. Patents:

Usable Depth: 8.09 in. U.S. Patent No. 7,572,975 Volume: 2061 cu. in. Country of Origin: United States of America

#### **FEATURES**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus nonmetallic mounting brackets and a gasket system encased in a continuous channel on the cover.

### **APPLICATION**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### **STANDARDS**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









#### **COLOR**

**RAL** 7035 - Gray

### **MATERIAL**

ULTRAGUARD® Fiberglass reinforced polyester compression molded SMC box and Cover

## **MOUNTING**

Nonmetal flange fastened to back side brass insert

# **ENCLOSURE ACCESSORIES**

Back Panels, Hinged Front Panel, Hole Plugs, Vent Kits, and Pole Mount Kit

### **ADDITIONAL MATERIALS**

316 stainless steel external hardware (hinges, latches and fasteners)

Polycarbonate mounting brackets

Plated carbon steel internal hardware

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system