# **AM24200RTW**



# **Product Description**

Wall mount enclosure assembly

Cover Type: Twist Latch Hinged Window Cover

**Brand:** Control Series Catalog #: AM24200RTW

Height: 24 in. Width: 20 in. Depth: 10 in.

Usable Depth: 10.54 in. Volume: 5702 cu. in.

Carton Quantity: 1 Carton Weight: 24 lb.

UPC: 085339924067 UNSPSC: 39121324

Country of Origin: United States of America

#### **FEATURES**

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel mounting brackets and a gasket system encased in a continuous channel on the cover.

### **APPLICATION**

Enclose and protect electrial and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

#### **STANDARDS**

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

#### Complies with:

- 1. EN / IEC 60204-1 and 60529 Type IP66
- 2. RoHS directive









## **COLOR**

RAL 7035 - Gray with clear window

## **MATERIAL**

ULTRAGUARD® Fiberglass reinforced polyester compression molded SMC box and cover with bonded clear polycarbonate window

## **MOUNTING**

Stainless steel feet fastened to back side brass inserts

## **ENCLOSURE ACCESSORIES**

Back Panels, Hinged Front Panel, Hole Plugs, Vent Kits, and Pole Mount Kit

## **ADDITIONAL MATERIALS**

316 stainless steel external hardware (hinges, latches and fasteners)

316 stainless steel mounting brackets

Plated carbon steel internal hardware

**Brass inserts** 

Polyurethane (FIP) Formed-In-Place gasket system