



AMXL403212L3PTW Product Description

Wall mount enclosure assembly

Cover Type: 3-Point Lockable Latching Handle Hinged Cover

Brand: Control XL™
Catalog #: AMXL403212L3PTW

Carton Quantity: 1
Carton Weight: 79 lb.

Height: 39.73 in.
Width: 31.23 in.
Depth: 11.50 in.
Usable Depth: 11.41 in.
Volume: 14269 cu. in.

UPC: 08533999805
UNSPSC: 39121324
Country of Origin: India



VIDEO

FEATURES

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

APPLICATION

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

STANDARDS

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



COLOR

RAL 7035 - Gray

ENCLOSURE ACCESSORIES

Back Panels, Hinged Front Panel, Hole Plugs, Vent Kits, and Pole Mount Kit

MATERIAL

ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

ADDITIONAL MATERIALS

Plated carbon steel internal hardware

316 stainless steel external hardware

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system

MOUNTING

Nonmetal feet fastened to back side brass insert