



## AMXL403212L3PTW

### Product Description

Wall mount enclosure assembly

**Cover Type:** 3-Point Lockable Latching Handle Hinged Cover

**Brand:** Control XL™  
**Catalog #:** AMXL403212L3PTW

**Carton Quantity:** 1  
**Carton Weight:** 79 lb.

**Height:** 39.73 in.  
**Width:** 31.23 in.  
**Depth:** 11.50 in.  
**Usable Depth:** 11.41 in.  
**Volume:** 14269 cu. in.

**UPC:** 08533999805  
**UNSPSC:** 39121324  
**Country of Origin:** India



VIDEO

### FEATURES

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus molded-in mounting flanges and a formed-in-place polyurethane gasket system.

### APPLICATION

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### STANDARDS

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



### COLOR

RAL 7035 - Gray

### ENCLOSURE ACCESSORIES

Back Panels, Hinged Front Panel, Hole Plugs, Vent Kits, and Pole Mount Kit

### MATERIAL

ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and cover with bonded clear polycarbonate window

### ADDITIONAL MATERIALS

Plated carbon steel internal hardware

316 stainless steel external hardware

### MOUNTING

Nonmetal feet fastened to back side brass insert

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system