



## AM743SF



### Product Description

Pendant type junction box assembly

**Cover Type:** Lift-Off 4-Screw Solid/Opaque Cover

**Brand:** Small Junction Box

**Catalog #:** AM743SF

**Carton Quantity:** 1

**Carton Weight:** 2 lb.

**Height:** 6.01 in.

**Width:** 3.31 in.

**Depth:** 3.13 in.

**Usable Depth:** 3.06 in.

**Volume:** 71 cu. in.

**UPC:** 085339910091

**UNSPSC:** 39121324

**Country of Origin:** United States of America

### FEATURES

Non-corrosive, non-conductive, light weight with lower installation cost, easy to modify and longer life cycle compared to steel. Rigid design with back panel inserts plus stainless steel fasteners and an formed in place polyurethane gasket system encased in a continuous channel on the cover.

### APPLICATION

Enclose and protect electrical and electronic controls, instruments or components for indoor and outdoor applications. Especially well suited for extreme temperature and corrosive environments.

### STANDARDS

UL 508A, UL 50 and UL 50E Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. E120175

CSA-C22.2 No. 14 and CSA C22.2 No. 94 Types 1, 2, 3, 3R, 4, 4X, 12 and 13; File No. 89590

Complies with:

1. EN / IEC 60204-1 and 60529 Type IP66
2. RoHS directive



### COLOR

RAL 7035 - Gray

### ENCLOSURE ACCESSORIES

AM series panels

### MATERIAL

ULTRAGUARD® Fiberglass reinforced polyester - compression molded SMC box and Cover

### ADDITIONAL MATERIALS

316 stainless steel external hardware (hinges, latches and fasteners)

Plated carbon steel internal hardware

Brass inserts

Polyurethane (FIP) Formed-In-Place gasket system

### MOUNTING

No mounting brackets supplied