



## 9373-FR



VIDEO

### Product Description

4" dia. round fan support box for use with nonmetallic sheathed cable

**Catalog #:** 9373-FR

**Width:** 4 in.

**Depth:** 6 in.

**Volume:** 16.5 cu. in.

**Type of Installation:** Old or New Work  
**Round Ceiling Box**

**Carton Quantity:** 40

**Carton Weight:** 16 lb.

**UPC:** 085339782544

**UNSPSC:** 39121316

**Patents:**

U.S. Patent No. 6,365,831 B1

U.S. Patent No. 7,531,742

**Country of Origin:** United States of America

### FEATURES

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

### APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Black

### ADDITIONAL MATERIALS

Plated carbon steel fasteners

### MATERIAL

Polycarbonate

### SUPPORT RATING

110 lbs fixture support and 70 lbs fan support

### MOUNTING

Bottom mount