



9335-NGC2



VIDEO

Product Description

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 9335-NGC2

Carton Quantity: 50
Carton Weight: 26 lb.

Width: 3.5 in.
Depth: 2-15/16 in.
Volume: 20.5 cu. in.
Type of Installation: New Work
Round Ceiling Box

UPC: 085339411901
UNSPSC: 39121316
Country of Origin: United States of America

FEATURES

Machine tapped fixture holes, ground strap, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

APPLICATION

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Nail-on with fetter ring nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Plated carbon steel clamp and fasteners

Galvanized ground strap with plated carbon steel fastener and green plated carbon steel ground screw

SUPPORT RATING

50 lbs fixture support