



9355-K



VIDEO

Product Description

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 9355-K

Carton Quantity: 48
Carton Weight: 19 lb.

Width: 3-1/2 in.
Depth: 2-3/4 in.
Volume: 22 cu. in.
Type of Installation: Old Work
Round Ceiling Box

UPC: 085339682912
UNSPSC: 39121316
Country of Origin: United States of America

FEATURES

Machine tapped fixture holes, round exterior for easy cut-in, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

APPLICATION

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support - flange mount) and ceilings (50 lbs. fixture support - bottom mounted)

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

ADDITIONAL MATERIALS

Polyvinyl chloride clamps

MATERIAL

Fiberglass reinforced polyester BMC

SUPPORT RATING

15 lbs fixture support - flange mount or 50 lbs. fixture support - bottom mounted

MOUNTING

Bottom mount button holes or flange holes