



PC213-16



Product Description

3.5" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: PC213-16

Carton Quantity: 24
Carton Weight: 17 lb.

Width: 3-1/2 in.
Depth: 2-13/16 in.
Volume: 21 cu. in.
Type of Installation: New Work
Round Ceiling Box

UPC: 085339983040
UNSPSC: 39121316
Patents:
U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Machine tapped fixture holes

APPLICATION

New work residential construction 2 HR fire resistive walls and ceilings (50 lbs. fixture support)

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

MATERIAL

Polycarbonate

SUPPORT RATING

50 lbs fixture support

MOUNTING

Adjustable bar hanger - max 16" on center Joist application