



## 9338-E



VIDEO

### Product Description

3.5" dia. round fixture support (15 lbs.) box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 9338-E

**Carton Quantity:** 50  
**Carton Weight:** 14 lb.

**Width:** 3-1/2 in.  
**Depth:** 2 in.  
**Volume:** 14 cu. in.  
**Type of Installation:** Old Work  
**Wall Box**

**UPC:** 085339460008  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

### FEATURES

Machine tapped fixture holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps bulk packed

### APPLICATION

Old work residential construction 2 HR fire resistive walls (15 lbs fixture support)

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Beige/tan

### MATERIAL

Fiberglass reinforced polyester BMC

### MOUNTING

Metal ears

### ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

Polyvinyl chloride clamps

### SUPPORT RATING

15 lb fixture support