



## 2302-HNKV2



VIDEO

### Product Description

Two gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™ - Vapor Seal  
**Catalog #:** 2302-HNKV2

**Carton Quantity:** 6  
**Carton Weight:** 6 lb.

**Height:** 3-3/4 in.  
**Width:** 4 in.  
**Depth:** 3-7/16 in.  
**Volume:** 37 cu. in.  
**Type of Installation:** New Work  
**Wall Box**  
**Number of Gangs:** 2

**UPC:** 085339927112  
**UNSPSC:** 39121308  
**Patents:**  
U.S. Patent No. 6,908,003 B2  
**Country of Origin:** United States of America

### FEATURES

Polyurethane flange for double drywall offset, machine tapped device holes, slot provision for low voltage divider, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

### APPLICATION

New work residential construction 2 HR fire resistive walls - air-sealed electrical boxes for envelop walls in Energy Star homes

### STANDARDS

ANSI / UL 514C: File No. E30594



NEMA OS 4 - Energy Efficient Air-Sealed Boxes for Electrical Applications



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

### COLOR

Beige/tan

### MATERIAL

Fiberglass reinforced polyester BMC

### MOUNTING

Nail-on backside HN hanger bracket for adjusting to additional wall/ceiling substrate

### ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

Polyvinyl chloride clamps

Polyurethane flange