



# 4304-2Z4K



VIDEO

## Product Description

Four gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 4304-2Z4K

**Carton Quantity:** 12  
**Carton Weight:** 17 lb.

**Height:** 3-3/4 in.  
**Width:** 7-1/2 in.  
**Depth:** 3-9/16 in.  
**Volume:** 75 cu. in.  
**Type of Installation:** New Work  
**Wall Box**  
**Number of Gangs:** 4

**UPC:** 085339175612  
**UNSPSC:** 39121308  
**Country of Origin:** United States of America

## FEATURES

Machine tapped device holes, slot provision for low voltage divider, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

## APPLICATION

New work residential construction stud face mounted 2 HR fire resistive walls

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Beige/tan

## ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

## MATERIAL

Fiberglass reinforced polyester BMC

Polyvinyl chloride clamps

## MOUNTING

Stud mount "Z" hanger bracket both sides with 1/2" offset