



## 9367-EW



VIDEO

### Product Description

Single gang electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** 9367-EW

**Carton Quantity:** 50  
**Carton Weight:** 18 lb.

**Height:** 3.25 in.  
**Width:** 2.38 in.  
**Depth:** 1.69 in.  
**Volume:** 16 cu. in.  
**Type of Installation:** Old Work  
**Wall Box**  
**Number of Gangs:** 1

**UPC:** 085339756019  
**UNSPSC:** 39121309  
**Country of Origin:** United States of America

### FEATURES

Machine tapped device holes, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

### APPLICATION

Old work wall construction - side cube body design for use in basement type furring strip shallow walls

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

#### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Beige/tan

### ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

### MATERIAL

Fiberglass reinforced polyester BMC

### MOUNTING

Metal wing brackets/metal ears wall compression