



9372-NMHK



VIDEO

Product Description

Two gang electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: 9372-NMHK

Carton Quantity: 48
Carton Weight: 26 lb.

Height: 3-3/4 in.
Width: 4 in.
Depth: 2-3/4 in.
Volume: 30 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 2

UPC: 085339106838
UNSPSC: 39121309
Country of Origin: United States of America

FEATURES

Machine tapped device holes, 3/16" panel stops, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures, Speed "K" Clamps factory installed

APPLICATION

Manufactured housing construction 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails with 3/16" panel stops opposite side

ADDITIONAL MATERIALS

Carbon steel fasteners

Polyvinyl chloride clamps