



P-108H



Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: P-108H

Carton Quantity: 24
Carton Weight: 3 lb.

Height: 3-3/4 in.
Width: 2-5/16 in.
Depth: 1-1/4 in.
Volume: 8 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 1

UPC: 085339249184
UNSPSC: 39121308
Country of Origin: United States of America

FEATURES

Molded-in splined device holes

APPLICATION

New work residential construction 2 HR fire
resistive walls & ceilings

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379
(Outlet boxes and fittings classified for fire resistance)*

COLOR

Black

MATERIAL

Polyvinyl Chloride

MOUNTING

Molded-in side mount hanger bracket