



## RD-42



VIDEO

### Product Description

Range/dryer electrical box for use with nonmetallic sheathed cable

**Brand:** fiberglassBOX™  
**Catalog #:** RD-42

**Height:** 3-3/4 in.  
**Width:** 4 in.  
**Depth:** 3-13/16 in.  
**Volume:** 42 cu. in.  
**Wall Box**

**Carton Quantity:** 24  
**Carton Weight:** 22 lb.

**UPC:** 085339129073  
**UNSPSC:** 39121309  
**Country of Origin:** United States of America

### FEATURES

Machine tapped holes for 2-position device ,  
internal metal clamp for easy wire adjustment,  
offset gauge marks, leveling ribs, rigid hard box  
construction, no distortion with high  
temperatures, shatter resistant with low  
temperatures

### APPLICATION

New work residential construction 2 HR fire  
resistive walls

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's  
CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

### COLOR

Beige/tan

### ADDITIONAL MATERIALS

Carbon steel fasteners

### MATERIAL

Fiberglass reinforced polyester BMC

Plated carbon steel clamp and fasteners

### MOUNTING

Angled mid nails with fether ring nails