



RD-42SS



VIDEO

Product Description

Range/dryer electrical box for use with nonmetallic sheathed cable

Brand: fiberglassBOX™
Catalog #: RD-42SS

Height: 3-3/4 in.
Width: 4 in.
Depth: 3-13/16 in.
Volume: 42 cu. in.
Wall Box

Carton Quantity: 24
Carton Weight: 22 lb.

UPC: 085339129059
UNSPSC: 39121309
Country of Origin: United States of America

FEATURES

Machine tapped holes for 2-position device , internal metal clamp for easy wire adjustment, offset gauge marks, leveling ribs, rigid hard box construction, no distortion with high temperatures, shatter resistant with low temperatures

APPLICATION

New work residential construction - steel or wood studs 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Beige/tan

MATERIAL

Fiberglass reinforced polyester BMC

MOUNTING

Angled mid nails with fether ring nails

ADDITIONAL MATERIALS

Carbon steel fasteners

Plated carbon steel clamp and fasteners