



## SB-2



VIDEO

### Product Description

Two gang adjustable electrical box for use with nonmetallic sheathed cable

**Brand:** SLIDERBOX®  
**Catalog #:** SB-2

**Height:** 3-3/4 in.  
**Width:** 4 in.  
**Depth:** 3-9/16 in.  
**Volume:** 42 cu. in.

**Type of Installation:** Old or New Work  
**Wall Box**  
**Number of Gangs:** 2

**Carton Quantity:** 24  
**Carton Weight:** 9 lb.

**UPC:** 085339945017  
**UNSPSC:** 39121308  
**Patents:**  
U.S. Patent No. 7,855,338

U.S. Patent No. 6,365,831 B1  
**Country of Origin:** United States of America

### FEATURES

Molded-in splined device holes, adjustable slider plate for additional wall substrate thickness, slot provision for low voltage divider, rectangular exterior for easy cut-in, leveling ribs, offset gauge marks

### APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings

### STANDARDS

ANSI / UL 514C: File No. E30594



### FIRE CLASSIFICATION

#### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

#### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

### COLOR

Beige/tan

### ADDITIONAL MATERIALS

Carbon steel fasteners

### MATERIAL

Polycarbonate

### MOUNTING

Internal screws with adjustable slider plate for substrates 1/2" to 1 3/8"